

**STARVIS**

2 MP & 5 MP IR IP Mini Domes w/ GXi Embedded Intelligence

GANZ
PixeIPro WITH **GXi**
TECHNOLOGY

ZN1A-M4DTFN3 / M6DTFN3

Features:

- 2 & 5 Megapixel @ 30fps
- 1/2.8" SONY STARVIS Exmor Sensor
- True Day / Night and WDR
- 2.8mm Fixed Lens
- VCA Technology Video Analytics
- Superior Low Light Performance
- SMART Bitrate Control & Region of Interest
- 2 IR LEDs up to 25 Meter

ZN1A-M4/6DTFN3

2 & 5 Megapixel IR IP Mini Domes w/ GXi Embedded Intelligence

 Specifications (Part 1)

Model	ZN1A-M4DTFN3	ZN1A-M6DTFN3	
Camera	Image Sensor	1/2.8" SONY STARVIS Exmor 2.13MP CMOS	1/2.8" SONY STARVIS Exmor 5MP CMOS
	Effective Pixels	1920 x 1080	2592 x 1944
	Scanning System	Progressive scanning	
	AGC Control	Auto	
	Iris Type	Auto-Iris	
	Minimum Illumination	Color: 0.03 Lux (DSS on) / B/W : 0 Lux (IR on)	
	Lens	2.8mm, F2.0 Fixed Lens	
	Angle of View	Horizontal: Approx. 115° / Vertical Approx. 64°	
	Shutter Speed	Automatic / Manual: 1/30 ~ 1/32,000, Anti-Flicker, Slow Shutter (1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10)	
	Day/Night Performance	True Day / Night (ICR)	
	Wide Dynamic Range	True WDR, 120dB	
	S/N Ratio	50 dB	
Video	Video Compression	H.265, H.264 Baseline, Main, High profile, MJPEG (Motion JPEG)	
	Multiple Profile Streaming Performance	1080p @30fps & D1(704x480 or 704x576) @30fps with H.264, H.265 & MJPEG	2592 x 1944 @30fps & 480 @30 fps with H.264, H.265 & MJPEG
	Max Resolution	1920 x 1080	2592 x 1944
	Video Bit Rate	100Kbps ~ 10Mbps Multi-rate for Preview and Recording	
	Bit Rate Control	Multi Streaming CBR/VBR @ H.264 (Controllable frame rate and Bandwidth)	
	Digital Noise Reduction	3D-DNR	
	ROI (Region of Interest)	Supported	
	SMART Bitrate Control	Supported	
	Other Image Processing	Configurable Exposure, White Balance, Sharpness	
	Privacy Mask	16 programmable zones	
Audio	Audio Streaming	Two Way	
	Audio Compression	G.711	
	Audio Input / Output	1 (Built-In Mic) / 0	
Event	Event Trigger	Motion, Temperature critical	
	Pre-Post Recording	Pre: 1~5 sec / Post: 1~240 sec	
	Event Notification	FTP, E-mail, SD card	
Network	Ethernet Standard	10 / 100 Base-T	
	IP	IPv4	
	Protocol	TCP/IP, UDP, AutoIP, RTP(UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3(MIB-2), ONVIF	
	Security	HTTPS (SSL), IP Filtering, 802.1x, Digest Authentication	
	Plug In	ONVIF Profile S, G, Q & T, CGI API	

All specifications are subject to change without notice.

ZN1A-M4/6DTFN3

2 & 5 Megapixel IR IP Mini Domes w/ GXi Embedded Intelligence

□ Specifications (Part 2)

Model	ZN1A-M4DTFN3	ZN1A-M6DTFN3
Embedded Intelligence (standard)	Analytics Engine	VCA Technology's advanced tracking algorithm with rich library of detection behaviors
	Detection Zones	40 zones (Multi-segment Polygons and Lines) in total
	Rules	60 rules in total
	Tamper Detection	Supported
Embedded Intelligence (optional)	Detection Behavior	Enter, Exit, Appear, Disappear, Stop, Direction, Dwell filter; Tailgating; Color Filter
	Logic Rules	Extends standard rules to allow various combinations of the inputs
	3D Behavior	Perspective Corrected Size and Speed Filters
	Object Classification	Configured Max./Min. object sizes and Max./Min. speeds
	People Tracking	Tracks individuals separately among overlapped multiple people
	Counting	20 counters in total
	Counting Line	High accuracy people and vehicle counting
	Counter Report	Generates counter reports based on the counter database
	Heatmap Report	Shows relative crowd density of the 24 hour period (criterion: midnight)
	Meta Data	JSON format, Plain XML Format
Edge Storage	Storage	1x MicroSD memory card slot / microSDHC / microSDXC (card not included)
Physical	Material	Aluminum Die-Casting; White
	Language	English
	IR LEDs	2 Smart IR LEDs (25 meter)
	Power Source	12VDC, PoE (IEEE 802.3af)
	Power Consumption	12VDC Max. 3.7W / PoE Max 5.5W
	Operating Conditions	[12VDC/PoE] -4°F ~ 122°F (-20°C ~ 50°C) / Humidity 10% to 90% RH (non-condensing)
	Dimensions	4.1" (Ø) x 2.4" / 105mm (Ø) x 60.7mm
	Weight	0.9 lbs / (400g)
	Certifications	FCC, CE, BIS, EN, IP66, IK10

All specifications are subject to change without notice.