

ZN10-MB2F28-IRE

2MP, 2.8 Fixed lens Bullet Camera



Key Features

- 1/2.8" High-Quality SONY CMOS Sensor
- 2MP, 2.8mm Fixed Lens
- STARVIS Series Back-Illuminated Progressive Scan Sensor
- Infrared Night Vision up to 50 Meters
- Multi-Stream Video Output
- Supports 1 input and 1 output channel for two-way audio communication.
- IP66/IP67 Weatherproof Rating
- IK10 Vandal Resistance
- CE, FCC, RoHS Compliant

Technical Specifications

Camera	
Image Sensor	1/2.8" Progressive Scan Sony CMOS
Max. Resolution	2MP (1920 x 1080)
Electronic Shutter	Auto/Manual, 1/15s - 1/100000s
Min. illumination	Color: 0.01 Lux @F1.2 (AGC ON) B/W: 0 Lux @ (IR LED ON)
Day & Night	IR cut filter
IR Distance	Up to 30m
IR Led Wavelength	850nm
IR On/Off Control	Auto/Manual
DORI AS PER IEC 62676 - IV	D: 38 m, O: 16 m, R: 8m, I: 4 m
Pan / Tilt / Rotation Range	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°
Lens	
Lens Type	Fixed Focus
Iris	Fixed
Focal Length	2.8mm
Focus Range	0.3m to infinity
F Number	F 1.6 / F 2.0
Angle of View	H: 106.9°, V: 56.9°, D: 127.9°
Video	
Streaming Capability	4 Streams
Stream/Frame Rate	Profile 1: 1920x1080p(2MP) @30fps (H.265/ H.264) Profile 2: D1 @30fps (H.265/H.264) Profile 3: 1920x1080p(2MP) @5fps (MJPEG) Profile 4: 720p @30fps (H.265/H.264/MJPEG)
Available Resolutions	1920 x 1080, 720p, D1, VGA, 2CIF, CIF
Video Compression	H.265, H.264, MJPEG
Bit Rate Control	CBR/VBR
Bit Rate	128 kbps-8Mbps
Digital Zoom	16x
Smart Encode	Support
Image	
Image Adjustment	Rotation/ Saturation/ Contrast/ Sharpness/ Brightness/ Hue/ White Balance
White Balance	Auto/Manual
Day/Night Setting	Auto, Day, Night, Time
Noise Reduction	2D/3D DNR
Image Enhancement	HLC, BLC, Defog
Wide Dynamic Range	True WDR
S/N Ratio	>70dB
Motion Detection	Support
Privacy Masking	Support upto 3 Zone

Smart Function	
Smart Events	Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion
IP Conflict	Yes
Network Disconnect	Yes
Storage Full	Yes
Upload Image / Video	SD, NAS, SFTP
Notifications	E-mail, SMS, TCP
Audio	
Compression	G.726 and G.711μ
Two-way Audio	Support
Network	
Protocols	TCP/IP, HTTP, ARP, DSCP, QoS, DHCP, DNS, DDNS, RTP, RTCP, RTSP, PPPOE, SMTP, NTP, HTTPS, TLS/SSL, SFTP, ICMP, IGMP, 802.1x, SNMP, UPnP, Bonjour, UDP
ONVIF Profiles	S, G, and T
Web Viewer	Supported in IE 8.0-11.0, Firefox 15.0-47.0, Chrome 20.0-54.0
Interface	
Network Interface	10Base-T/100BaseTX Ethernet (RJ-45)
Audio Interface	1ch Input, 1ch Output
SD Card Slot	Built-in, up to 512GB
Electrical	
Power Supply	12V (DC); 802.3af (PoE)
Power Consumption	Max 5.5 W
Operating Temperature	-30°C ~ 60°C
Storage Temperature	-30°C ~ 60°C
Operating Humidity	Less than 95% RH (non-condensing)
Ingress Protection	IP67
Certifications	NDAA Compliant, BIS, CE, IP67, FCC Part-15 Subpart – B, ONVIF S G & T, IK10, UL, NEMA 4X**, Essential Requirement (ER) by STQC, Delhi
Casing	Metal
Dimensions	159.7mm x 74.3mm
Net Weight	500gms

Dimensions (mm)

